Planning Noise Advice Document: Sussex

Final Released: 2021

Contents

1.0 Introduction 3
1.1 Aims and Objectives 3
1.2 Document Overview 4

2.0 Basic Principles 9
2.1 Good Design 9
2.2 Noise Reports 10
2.3

P

P

1.1.5. This document will be updated from time to time to take account of any new standards, guidance and policy. Where any standards, guidance and policy referred to in this document have been revised please use the latest version.

1.2 Document Overview

1.2.1. The document initially introduces some basic principles in Chapter 2.0.

1.2.2. The document then goes on to consider noise impact from potentially noisy sources: Industrial and commercial sounds (Chapter 3.0); entertainment premises (Chapter 4.0); and sites used for sports and recreation (Chapter 5.0).

1.2.3. New noise sensitive developments are discussed in more detail in Chapter 6.0.

1.2.4. Finally, transport schemes are discussed in Chapter 7.0.

1.2.5. For ease, where standards and codes of practice are referred to in this document they are fully referenced in Annex 1. A glossary appears in Annex 2. Annex 3 references relevant documents including guidance, standards and codes of practice.

1.2.6. To assist determine which sections of this document are relevant to a development Table 1 below provides a quick guide. For mixed use developments multiple sections apply.

Table 3: How to

should include consideration of the most appropriate positioning of the noise source/ sensitive receptor within the chosen site boundary.

III. If all reasonable steps have been taken to reduce the impact of the noise but the development is still likely to lead to adverse effects, then adequate mitigation should be employed. Appropriate mitigation could include changes to the site layout, a noise management plan, the construction of noise barriers, and as a last resort, the insulation of buildings. In the exceptional circumstances where windows are required to be kept closed to achieve an acceptable internal noise climate, then the provision of an alternative form of natural ventilation will be required to aid thermal comfort. If this is impracticable then a MVHR system with fully automated summer bypass may

existing noise environment, and the likely impact of the proposed development. A report lacking vital information or containing misleading information may ultimately delay the whole planning process whilst clarification or further

VII. Sound samples should be obtained and made available to support the assessment as appropriate.

2.3 Information Required to support a Planning Application

2.3.1. New noise generating development may vary greatly in size and scale. Advice should always be sought from the LPA if it is unclear whether the development requires a comprehensive noise report, but as a general rule the following should be considered where sensitive receptors could be affected:

- Larger scale developments or those including potentially noisy mechanical and electrical plant, which are to be located in proximity to noise sensitive receptors will generally require a noise report, following the advice given in section 2.2.

- Small scale developments, such as a single extraction unit or air conditioning unit may not always require a noise report. However in order to help the LPA to decide whether it is likely to conform to an appropriate souvelt

ensure transparency.

2.4 Prediction Methods/Modelling

2.4.1. There are a range of prediction and modelling tools available for determining the impact from noise sources. Where modelling is to be used, the method should be discussed and considered against current standards and practices. Information including details of inputs and calculations used, plus any assumptions made within the modelling/prediction exercise should be explained clearly and uncertainty discussed.

2.4.2. Modelling and predictions should be undertaken in two stages: with and without mitigation. For instance, if particularly noisy plant is likely to be used, then predictions should be made for both the untreated plant and with attenuation measures in place.

2.4.3. The receptors used for the modelling should coincide with background monitoring locations. Where they do not, a detailed rationale should be provided.

2.5 Minimum Considerations for Noise Sensitive Development

2.5.1. For a new noise sensitive development near an existing source of transport noise (road, rail, ports or aircraft) the L_{Aeq} (16hr day and 8hr night), should be measured. In addition, suitable shorter term L_{Aeq}, L_{A90}, L_{A10} and L_{Afmax} would be expected in order to give a clearer picture of the existing noise environment.

2.5.2. Where the external L_{Afmax} sound levels are likely to exceed 60 dB during the night period, overnight monitoring will be necessary. A specific $L_{Afmax,1\ minute}$ risk assessment shall be provided for the whole night period. This could also apply to extensions/ alterations to existing development.

2.5.3. For a new noise sensitive development next to a commercial noise source, where practical, each existing potential noise source would need to be measured separately and details provided of the hours of operation, the L_{Aeq}, the tonality, character, impulsivity and/or intermittency of the noise (see BS 4142) and the hours of occurrence. The existing background noise level (L_{A90}) will also have to be measured with and without the commercial noise sources in operation in accordance with BS 4142. This could also apply to extensions/ alterations to existing development.

3.0 Industrial and Commercial Sound Sources

3.1 Scope

3.1.1. This section covers sound sources of an industrial and commercial nature. It refers to sound sources which are covered by the British Standard BS 4142:2014 + A1: 2019 ³0HWKRGV IRU 5DWLQJ DQG $VVHVVLQJ ,QGXVWULDO DQG &RPPHUFLDO 6RXQG´ $SSURSULDWH VRXQG VRXUFHV covered by BS 4142:2014 are detailed in section 1.1 of the scope of the Standard and include:

- Sound from industrial and manufacturing processes
- Sound from fixed installations, which comprise mechanical and electrical plant
- Sound from loading and unloading goods
- Sound from mobile plant and vehicles that are an intrinsic part of the overall sound emanating from the premises or process e.g. fork-lift truck movements etc.

3.1.2. This section would also be appropriate for some aspects of waste and minerals developments (see Annex 1, of this document, for standards applicable to waste and minerals sites).

3.2 Guidelines and Criteria

3.2.1. The rating level of the industrial or commercial sound source should, where practicable, achieve a level no greater than the representative background sound, when measured in accordance with BS 4142:2014 + A1: 2019. There may be instances, for specific sites, where a rating level below background is deemed appropriate. This can be determined through discussion with the Local Planning Authority (LPA). A rating level below background may be required if there are concerns for potential noise creep, for example in a High Street setting. It is considered that meeting this criterion would avoid adverse noise impacts, in the interests of ensuring a good standard of amenity and protecting human health. Where these criteria are not attainable, the noise report should explain why, and how best practicable means will be implemented to control noise in order to satisfy the LPA that the development is acceptable. At all times the reports shall have regard to the context.

3.2.2. To assist in the interpretation and application of BS 4142:2014+A1:2019, the applications for kennels and other animal boarding and breeding establishments, being commercial in nature, are considered to be within scope of BS4142. However, the sounds of animals in purely a residential setting are not. Similarly there may be other occasions when sources giving rise to sounds of an industrial or commercial nature are located in a non-commercial setting. In such

circumstances the local authority should be consulted to confirm whether a BS4142 assessment is acceptable. An example of such a source is a swimming pool pump house on a residential premises.

3.3 Sound Insulation Between Domestic and Non-Domestic Premises

3.3.1.

ranges, then the predicted acoustic performance of any scheme of sound insulation design should be conducted over a more extensive frequency range. The overall building design acoustic performance shall be demonstrated across the frequency range of at least 31.5Hz to 3150Hz at each $^{1}/_{3}$ octave band.

3.4 Vibration

3.4.1. In some instances, due to the proximity of potentially disturbing vibration sources, such as a railway line or a commercial activity, a Vibration Impact Assessment shall be submitted to the Local Planning Authority.

3.4.2. Consideration should be given to recommended threshold Vibration Dose Values 9 ' 9 ¶ V D V S U H V 6 4 2 W H G L Q % 6 H W R (Y D O X D W L R Q R I + ([S R V X U H W R 9 L E U D W L R Q L Q % 6 G L Q J V or other appropriate mitigation measures are required so that appropriate threshold

4.0 Entertainment Premises

4.1 Scope

4.1.1. This chapter is a guide to the noise issues associated with premises used for public entertainment, including clubs, pubs, bars, restaurants and other recreational uses such as wedding venues and conference facilities.

4.1.2. Most of these types of premises will also require a Premises Licence in accordance with the Licensing Act 2003. The applicant should approach the Licensing Authority as early as possible to ensure that the proposed final use of the premises complies with local Licensing Policy.

4.1.3. Planning permission, building control approval and licensing regimes are required

4.3.4. Where the proposed development shares a party wall or floor or is structurally connected to adjoining residential dwellings or other noise-sensitive premises, particular attention should be given to structure - borne noise and vibration. Full details of potential impacts and how these have been mitigated should be provided with the planning application.

4.3.5. Doors and windows will ofte4JET227.8MC338.8MCID 1/Lan3 (en-US)>BDC BT1 0 0 1570.94

4.3.11. Noise Management Plans should be submitted as part of the application addressing all the above points and any

a(a)-e(o)4(n)-3t(a)-3(b) 3(b8)itig(e)-364(it)106n-3(s sh)m.(n)-3(d)-3( )]TJETBT1 0 0 1 680.62 796.44 T n(d)6(ad

5.0 Outdoor Sports and Recreation

5.1 Scope

5.1.1. This section covers sport and leisure activities which take place outside, such as clay target shooting, off road motorcycle sports and model aircraft flying, as well as the use of multi-use games areas (MUGAs), all weather pitches (AWPs) and skate parks.

5.2 Considerations

5.2.1. In some circumstances, the noise levels generated from outdoor sport and recreation are likely to be higher than would normally be accepted for other development consents, such as industrial processes, because of the characteristics of the noise generated, the controls that are possible, and the pattern of use.

5.2.2. For these activities, the LPA will need to take account of how frequently the noise will be generated and how disturbing it will be. Therefore, clear details of the proposed development are crucial.

5.2.3 It is common for outdoor sport and recreation to take place in suburban and rural locations, where existing ambient noise levels can be very low and therefore, such activities can greatly impact on surrounding amenity. The selection of suitable sites is very important and care should be taken at an early stage to ensure that the chosen location is appropriate.

5.3 Codes of Practice

5.3.1 Some of the more common recreational activities have associated Codes of Practice. While these Codes of Practice do not have the force of law, they do provide important guidance on likely noise impacts and advice on setting suitable controls.

5.3.2. Any noise report required to assess likely noise impact should properly consider any relevant Codes of Practice.

Current Codes of Practice are listed in Annex 3.

5.4 Multi Use Games Areas (MUGAs)

5.4.1. Currently, there are no Codes of Practice for controlling noise from MUGAs.

5.4.2. Planning applications for such facilities can give rise to a range of amenity concerns, especially noise, particularly where they are proposed in residential neighbourhoods. Noise impacts from MUGAs can vary depending on a number of factors including the hours of operation, location, design, size of the facility, the level of use, appropriate maintenance and location of spectators. Consequently, H D U O \ J X L G D Q F H V K R X O G E H V R X J K W I U R P W K H / 3 $, Management Plan is submitted with planning applications for MUGAs, covering issues such as hours and days of use, community liaison, complaints procedures, student briefings and preventing unauthorised use.

- Consideration should be had to the influence of individual LA max levels which should be obtained by measurement using short 5 or 1 minute periods as agreed with the LPA.

- Road texture, speed and gradient, plus existing noise barriers and land topography

6.5.4. While noise mitigation measures can be used to achieve suitable internal sound levels, preference is to be given to criteria based on windows being partially open.

6.5.5 Where the property is at risk of overheating an overheating assessment shall be conducted in accordance with Acoustics Ventilation and Overheating (AVO) 5 H V L G H Q W L D O ' H V L J Q * X L G H - D Q X D U \ D Q G & , % 6 (the Assessment of Overheating Risk in Homes (TM59: 2017).

6.5.6.

6.6 New Noise Sensitive Developments Near To Existing Industrial/Commercial noise sources

6.6.1. Careful consideration will need to be given to proposals that are likely to site new noise sensitive developments near to existing industrial, commercial, entertainment premises, airfields air ports and sea ports.

6.6.2. The 'agent of change' principle, the principle by which a person or business introducing a new land use is responsible for managing the impact of that change, will apply. The National Pl

Annex 1 ± Relevant Standards

Summary of key information from relevant national and international standards and guidance.

The following national and international documents provide further technical advice and guidance which should be referred to when making your application.

Development Category	Type of development	Relevant standards (See reference list below for full details)	Recommended noise thresholds at the most sensitive noise receptors.

Development Category	Type of development	Relevant standards (See reference list below for full details)	Recommended noise thresholds at the most sensitive noise receptors.

Annex 2 ± Glossary of Terms

Ambient Noise	Totally encompassing sound in a given situation at a given time composed of sound from all sources near and far. This is normally defined as $L_{Aeq,T}$ where T is an appropriate time assessment period.
Background Noise	Sometimes referred to as the background sound level, this is the ambient noise, in the absence of the noise under investigation, measured using time weighting ³)´ W K D W L V equaled or exceeded for 90% of the measurement time interval. Expressed as $L_{A90,T}$, w K H U H ³7´ U H I H U V W R W K measurement time interval in minutes.
dB(A)	The noise level in decibels, a measure including a correction for the sensitivity of the human ear defined in the International standard IEC61672:2003 and various national standards relating to the measurement of sound level. Measurements in dB(A) broadly agree with people ¶ assessment of loudness. A change of 3 dB(A) is the minimum perceptible under normal conditions, and a change of 10 dB(A) corresponds roughly to halving or doubling the loudness of a sound. The background noise level in a living room may be about 30 dB(A); normal conversation about 60 dB(A) at 1 metre; heavy road traffic about 80 dB(A) at 10 metres; the level near a pneumatic drill about 100 dB(A).
$L_{A90, T}$	This is the noise level exceeded for 90% of the measurement period. Often referred to as the background noise level.
$L_{Afmax, T}$	This is the maximum recorded sound pressure level within the relevant time interval (t) when the sound level meter is set to fast.
$L_{Aeq, T}$	This is the equivalent continuous A weighted sound pressure level and is the level of a notional steady sound which has the same acoustic energy as the fluctuating sound over a given time period. It often used as a measurement of environmental noise.

P

Planning Noise Advisory Document: